



STARCKE[®]
SCHLEIFMITTELWERK



Product Information

Aluminium Oxide Paper ERSTA Article-No. 514 C2 and 514 D

Base Stock	Flexible C- and robust D-weight latex paper, tear resistant
Bonding	514 C2: Special resin with stearate top coat free of any contaminating substances affecting the blending of the lacquer. 514 D: Special resin
Grain Type	Aluminium Oxide
Coating	Very open coat
Grain Size	514 C2: P 800 - P 150 514 D: P 120 - P 60, P 40
Manufactured Width	1.650 mm
Availability	Velcro discs, without and with holes for sanding machines with dust extraction, sheets, cut sheets, rolls and foam rolls.
Market Segment	Automotive industry – vehicle manufacture and repair. Dry sanding of electrocoat, primer and subsequent paint finish.
Advantages	<ul style="list-style-type: none">▪ The dust-repellent additive incorporated as top coat prevents premature clogging of the grain surface. Unlike conventional stearate coating this repellent effect is maintained throughout the product life.▪ Full resinoid bonding ensures excellent performance and durability.▪ It is best suited for grinding new generation water based lacquers.
Special feature	High durability, low clogging of the grain surface because of a 21 hole disc system in form 598. Best results will be achieved with the appropriate back-up pad also available from Starcke.

Starcke GmbH & Co. KG
Markt 10 | D-49324 Melle

Telefon +49 5422 966-0
Telefax +49 5422 966-301
E-Mail info@starcke.de

www.starcke.de

Metal

Car
Paint-
Shop

Wood

Paint