



STARCKE[®]
SCHLEIFMITTELWERK



Product Information

Aluminium Oxide Paper ERSTA Article-No. 544 C3

Base Stock	Flexible latex C-paper with high tear resistance
Bonding	Resin over resin with stearate top coat free of any contaminating substances affecting the blending of the lacquer.
Grain Type	Aluminium oxide
Coating	Very open
Grain Size	P 800 - P 80
Manufactured Width	1.650 mm
Availability	Velcro discs, without and with holes for sanding machines with dust extraction, sheets, cut sheets and rolls.
Market Segment	<p>Automotive industry – vehicle manufacture and repair. Dry sanding of electrocoat, primer and subsequent paint finish.</p> <ul style="list-style-type: none">■ Deburring and roughing of plastic parts such as bumpers, door mouldings and ornamental edgings.■ Sanding of file marks on car bodies.■ Aluminium and pigmented polyester paints and lacquers.
Advantages	<ul style="list-style-type: none">■ Full resinoid bonding ensures excellent performance and durability.■ The dust-repellent additive incorporated as top coat prevents premature clogging of the grain surface. Unlike conventional stearate coating this repellent effect is maintained throughout the product life.■ No contaminating substances are introduced to the sanding area.■ Aluminium oxide grain for maximum performance and durability.

Starcke GmbH & Co. KG
Markt 10 | D-49324 Melle

Telefon +49 5422 966-0
Telefax +49 5422 966-301
E-Mail info@starcke.de

www.starcke.de

Metal

Car
Paint-
Shop

Wood

Paint