


Product Information

PEARL GRINDING CP-Technology Article-No. A41 XP		ERSTA® 
Base Stock	Heavy X-weight polyester cloth Water, emulsion and oil resistant, also applicable for dry grinding	
Bonding	Resin over resin, medium strong	
Grain Type	Pearl Grinding (Aluminium Oxide)	
Coating	Close coat	
Grain Size	P 800, P 600, P 400, P 320, P 240, P 180, P 150, P 120, P 80, P 60	
Manufactured Width	1.650 mm	
Availability	Belts, wide belts	
Market Segment	<ul style="list-style-type: none"> ▪ Grinding of alloy and non-alloy steel. ▪ Repair and finish grinding of hot rolled coils and warm rolled sheet metal. ▪ Centerless grinding of round piping. ▪ Grinding of rectangular tubing. ▪ Grinding of welding seams of round and rectangular tube on medium hard contact wheels. ▪ Free hand grinding of welding seams of stainless steel tube. ▪ Wire grinding. 	
Advantages	<ul style="list-style-type: none"> ▪ Large amounts of grain for a long belt life. ▪ Consistent stock removal. ▪ Reduced scratch depth at the beginning of the grinding operation. ▪ Less surface roughness from start to finish. ▪ Good cutting power by using medium hard contact wheels and medium grinding pressure. 	

Starcke GmbH & Co. KG
Markt 10 | D-49324 Melle

Telefon +49 5422 966-0
Telefax +49 5422 966-301
E-Mail info@starcke.de

www.starcke.de

Metal

Car
Paint
Shop

Wood

Paint