


## Product Information

<b>PEARL GRINDING CP-Technology</b> <b>Article-No. B41 X</b>		
<b>Base Stock</b>	X-weight cotton cloth Water, emulsion and oil resistant, also applicable for dry grinding	
<b>Bonding</b>	Resin over resin, medium strong	
<b>Grain Type</b>	Pearl Grinding (Aluminium Oxide)	
<b>Coating</b>	Close coat	
<b>Grain Size</b>	P 400, P 320, P 240, P 180	
<b>Manufactured Width</b>	1.650 mm	
<b>Availability</b>	Belts, wide belts	
<b>Market Segment</b>	<ul style="list-style-type: none"> <li>▪ Grinding of alloy and non-alloy coils and sheet metal.</li> <li>▪ Finishing, decorative grinding of stainless steel coils and sheets.</li> <li>▪ Centerless grinding of round piping, steel cylinders and rolls.</li> <li>▪ Grinding of rectangular tubing.</li> <li>▪ Free hand grinding of welding seams of stainless steel tubing.</li> <li>▪ Wire grinding.</li> </ul>	
<b>Advantages</b>	<ul style="list-style-type: none"> <li>▪ Large amounts of grain for a long belt life.</li> <li>▪ Consistent stock removal.</li> <li>▪ Reduced scratch depth at the beginning of the grinding operation.</li> <li>▪ Less surface roughness from start to finish.</li> <li>▪ Good cutting power by using medium hard contact wheels and medium grinding pressure.</li> </ul>	

**Starcke GmbH & Co. KG**  
Markt 10 | D-49324 Melle

Telefon +49 5422 966-0  
Telefax +49 5422 966-301  
E-Mail [info@starcke.de](mailto:info@starcke.de)

[www.starcke.de](http://www.starcke.de)

Metal

Car  
Paint  
Shop

Wood

Paint